

INDEX

JANUARY THROUGH DECEMBER 1968—VOLUME 76

The Index of 1968 SAE Journal articles printed on these green pages is designed to make each moment you spend looking for information as productive as possible. The final objective is that you go back and read only articles that actually bear on your problem.

Here is the way to use the Index:

- Look up the subject heading of interest.
- Select all the titles under each subject heading that are of specific interest. Note the 6-digit number to the right of each title.
- In the Abstracts Section, which follows the Index, look up the selected Abstracts by means of the 6-digit numbers. (Abstracts are in numerical order.)
- Look up all the articles that the comprehensive Abstracts show should have information of use to you. (Each article can be located by means of the code number to the left of the 6-digit number in the Index. For example, JL68-9-47 means: SAE Journal, 1968, September, article starts on p. 47.)

This Index thus gives you two stages of prescreening before you start pulling old issues. In a way it is like making changes in the design stage of a product, rather than during production.

At each step of the way, the Index is tailored to help you find information rapidly and efficiently. First, the subject headings used are those agreed upon by 14 technical societies in an Engineers Joint Council project to simplify interdisciplinary terminology and indexing. As part of this approach, each article is indexed, on the average, under three to five headings.

In addition, you will note that your chances of finding the articles you need in the 1968 Journal Index are greatly increased because of the inclusion of cross-index headings. Most of these are more general terms, which are designed to lead you to more specific terms, which might cover articles of

direct interest to you. Two types of cross-index headings are used:

- "See" is used to relate broad concepts—under which there are no entries—to more specific terms under which entries will be found. For example:

Fuels

see:

Aviation Fuels
Diesel Fuels
Gasoline
Hydrocarbon Fuels
Jet Fuels
Liquefied Petroleum Gases
Liquid Propellants
Military Fuel Supplies

- "See also" is used to relate broad concepts—under which are listed only very general papers on the subject—to the specific terms under which entries will be found. For example:

Design

see also:

Bus Design
Construction Equipment Design
Passenger Car Design
Truck Design
Vehicle Design

An expanded title is used for each article under the subject headings. This helps in your first stage of prescreening, since the expanded title is really a very short Abstract. If you are looking only for background information in a new field, chances are you won't have to go beyond this point to find the articles you want.

Note that the inclusion of an Abstract for each technical article printed in SAE Journal during 1968 is a depth service that allows careful selection without your ever having to leave the green pages.

An Author Index is also included in these green pages so that you can find what articles have been contributed by a particular author.

SAE JOURNAL SUBJECT INDEX

SAE JOURNAL—JANUARY THROUGH DECEMBER, 1968—VOL. 76

A

Actuators

see also:

Servomechanisms

Flight control servo actuator with clutchless over-power mechanism but no rate or position feedback offers increased power, lower cost
JL68-6-72 684562

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Aerodynamics

Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571

Agricultural Machinery

Simple mathematical model shows how to increase cutting force reductions in horizontally vibrating plow blades
JL68-4-79 684541

Air Cargo Handling

Proposed submersible is tailored to rescue submarine personnel
JL68-5-74 684550

Air Conditioning

see:

Heaters

Aircooled Engines

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess
JL68-4-62 684536

Curtiss-Wright's rotary engine is light, compact, and smooth-running, characteristics which are usually associated with the aircraft gas turbine
JL68-5-67 684548

Aircraft

see:

Business Aircraft

Helicopters

Jet Lift Aircraft

Private Aircraft

STOL Aircraft

Supersonic Transports

Aircraft Design

Only deflected slipstream STOL aircraft, with its low cruise speed, matches DOC of today's jets, in design study
JL68-5-70 684549

Aircraft Equipment

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

New aluminum-cored printed circuit board, with copper-clad teflon-fiberglass dielectric layers has good heat, dielectric, and strength properties
JL68-2-63 684515

High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

Aircraft Instruments

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

Aircraft Operation/Aircraft Performance

Navion airplane with variable aerodynamic and inertial properties allows safe in-flight evaluation of aircraft handling qualities
JL68-6-62 684558

Aircraft Reliability

Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

Aircraft Selection

Only deflected slipstream STOL aircraft, with its low cruise speed, matches DOC of today's jets, in design study
JL68-5-70 684549

Aircraft Wings

see:

Wings/Aircraft

Airline Operations

Engineering problems associated with the SST, such as sonic boom, cosmic rays, fuel consumption, and airport requirements
JL68-1-60 684501

Airline safety can be improved by consideration of psychological factors
JL68-2-49 684509

Air Pollution

see also:

Crankcase Emission

Diesel Smoke

Exhaust Gases

Automobiles and air pollution—a program for progress
JL68-4-36 684531

Air pollution—the problem and the risks
JL68-5-47 684544

New tests help Ford evaluate oils for use in 1968 engines equipped with closed positive crankcase ventilation systems
JL68-5-56 684547

Recommendations 4-7 of federal government report on control of air pollution
JL68-6-42 684553

Roles of industry and government in air pollution control
JL68-7-39 684566

Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Air Terminals

Engineering problems associated with the SST, such as sonic boom, cosmic rays, fuel consumption, and airport requirements
JL68-1-60 684501

Altitude Simulation

Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

Aluminum

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Aluminum Alloys

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Ammonia

Spark ignition is more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608

Antiskid Devices

Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579

Asbestos

Perforated steel strip laminated with Buta N asbestos forms a new cylinder head gasket for high output engines
JL68-9-50 684590

Attitude Control

All fluidic autopilot with fluid sensing logic and control circuits gives 3-axis control. Flight test results equal conventional units
JL68-4-41 684532

Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Attitude control system keeps vela spacecraft spinning to give zero momentum vehicle
JL68-9-52 684591

Automatic Control

All fluidic autopilot with fluid sensing logic and control circuits gives 3-axis control. Flight test results equal conventional units
JL68-4-41 684532

Mobile automaton lives in and adapts to real world. It must avoid obstacles and seek and find power outlets to recharge its batteries
JL68-4-76 684540

Automatic Transmission Fluids

Automatic transmission fluids rated for oxidation resistance by new aluminum beaker test
JL68-4-59 684535

Auxiliary Power

Consideration of noise attenuation during design stage of turbine auxiliary power units gives most effective results
JL68-1-64 684502

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Axles

1969 passenger-car engineering trends
JL68-10-29 684596

B

Batteries

Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Bearings

Antifriction units, comprised of linear arrangements of ball or needle bearings may replace splined shafts to give truck driveline slip
JL68-1-68 684503

Beryllium

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

When all recycle metal blended with virgin powder to form beryllium is vacuum melted cast and attritioned a better product is obtained
JL68-9-66 684593

Biomechanics

Flight simulators will gain when motion system programs relate to body's motion cues
JL68-2-76 684519

Blowers

see:

Fans/Blowers

Bodies

Prototype of New York Safety Car developed, using only available components or those under advanced development
JL68-4-44 684533

1969 passenger-car engineering trends
JL68-10-29 684596

Bonding

see also:

Welding

Mechanical thermal pulse bonding controls process energies accurately and dynamically
JL68-3-79 684530

Booster Rockets

Survey of eight reusable launch vehicles shows cost weight availability date and critical technologies
JL68-8-36 684575

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Boron

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Brakes

see also:

Disc Brakes

National Bureau of Standards will play important part in development of government vehicle safety standards
JL68-1-80 684507

Surge Brakes keep trailer braking synchronized with tow car braking
JL68-2-64 684516

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

New test for brake linings gives reliable friction and wear data
JL68-7-50 684568

1969 passenger-car engineering trends
JL68-10-29 684596

Business Aircraft

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

C

Carbon Steels

Low carbon-boron steels favorably compare with SAE Grade 8, or medium carbon and alloy steels, also offer cold forming advantages
JL68-8-62 684583

Carburetors/Carburetion

Exhaust gas analysis used to figure fuel-air ratios
JL68-8-66 684584

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599

Casting

see also:

Continuous Casting

Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Clutches

SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

Coating

see also:

Finishing/Finishes Paints

Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Cold Forming

New fabricating techniques for plastics solid-phase forming and structural forming
JL68-6-36 684552

Low carbon-boron steels favorably compared with SAE Grade 8, or medium carbon and alloy steels, also offer cold forming advantages
JL68-8-62 684583

Combustion Chambers

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Composite Materials

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Compound Engines

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess
JL68-4-62 684536

Compressors

Comparison of a 3-shaft cycle turbine with a twin-spool compressor and a 2-shaft cycle as automotive powerplants
JL68-7-71 684572

Computer Applications

Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

Dynamic response of vehicle traversing random rough surfaces is analyzed. Exponentially weighted filter detrends input road surface prior to classification
JL68-5-78 684551

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Connectors

see:

Fasteners Joints

Construction Equipment Design

Fluidic technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573

Contamination
see also:

Air Pollution

Mechanical thermal pulse bonding controls process energies accurately and dynamically
JL68-3-79 684530

Continuous Casting

Surface finish is the main problem when continuous casting rimmed steels
JL68-11-31 684602

Control System

see:

Attitude Control
Automatic Control
Electric Control/Electronic
Flight Control
Governors
Hydraulic Control
Quality Controls
Speed Control
Turbine Engine Controls

Corrosion Prevention

New tests help Ford evaluate oils for use in 1968 engines equipped with closed positive crankcase ventilation systems
JL68-5-56 684547

Crankcase Emission

New tests help Ford evaluate oils for use in 1968 engines equipped with closed positive crankcase ventilation systems
JL68-5-56 684547

Crankcase Oils

New tests help Ford evaluate oils for use in 1968 engines equipped with closed positive crankcase ventilation systems
JL68-5-56 684547

Crash Research

Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500

Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525

Metal Cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546

Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581

Cylinders

see:

Combustion Chambers

D

Deorbiting

Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Design

see:

Aircraft Design
Construction Equipment Design
Passenger Car Design
Truck Design

Diesel Engines

see also:

Two Stroke Cycle Engines

Recommendations 4-7 of Federal Government report on control of air pollution
JL68-6-42 684553

Spark ignition is more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608

Diesel Smoke

Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522

Differential Gears

1969 passenger-car engineering trends
JL68-10-29 684596

Disc Brakes

Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579

Driver Behavior

Human engineering analysis is an aid to safe driving solutions
JL68-6-56 684556

Dangerous young drivers—why they are unsafe, and how their driving behavior can be improved by remedial programs
JL68-10-61 684597

Driveshafts

Antifriction units, comprised of linear arrangements of ball or needle bearings may replace splined shafts to give truck driveline slip
JL68-1-68 684503

Dynamometers

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

E

Economic Conditions

Engineering problems associated with the SST, such as sonic boom, cosmic rays, fuel consumption, and airport requirements
JL68-1-60 684501

Education

Improved internal combustion engine electives can change student-faculty attitudes
JL68-4-74 684539

Continuing education established as major SAE service program
JL68-9-68 684594

Engineering education goals set realistically in final report
JL68-11-40 684605

Ejectors

Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526

Elastomers

see:

Rubber/Synthetic Rubber

Electric Control/Electronic

Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

Concorde has electrically signalled, hydraulically powered flight controls with a mechanical backup system
JL68-3-47 684523

Mobile automaton lives in and adapts to real world. It must avoid obstacles and seek and find power outlets to recharge its batteries
JL68-4-76 684540

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Electric Equipment/Electronic

Low-cost power transistor—made by selecting appropriate encapsulant and encapsulating techniques—designed specifically for automotive circuits
JL68-4-66 684537

Mobile automaton lives in and adapts to real world. It must avoid obstacles and seek and find power outlets to recharge its batteries
JL68-4-76 684540

1969 passenger-car engineering trends
JL68-10-29 684596

Electric Vehicles

Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Electron Beams

Welding of low-carbon steels by electron beam process possible on a commercial basis once certain precautions are followed
JL68-9-70 684595

Electronic Packaging

New parallel gap welding electrode with integral heat sink eliminates overheating problems in joining flat pack leads to circuit boards
JL68-2-57 684513

New Aluminum-cored printed circuit board, with copper-clad teflon-fiberglass dielectric layers has good heat, dielectric, and strength properties
JL68-2-63 684515

Mechanical thermal pulse bonding controls process energies accurately and dynamically
JL68-3-79 684530

Tests on crosswire welds show that filleting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543

Engine Deposits

Bench test measures induction system deposit tendencies of fuels. Results do not correlate with those obtained by ASTM gum test now used.
JL68-2-50 684510

Chemical separation and identification of induction system deposit precursors permits new insight into the deposit forming mechanisms occurring in fuels.
JL68-2-52 684511

New tests help Ford evaluate oils for use in 1968 engines equipped with closed positive crankcase ventilation systems
JL68-5-56 684547

Engineers see also:

Education

Improved internal combustion engine electives can change student-faculty attitudes
JL68-4-74 684539

Continuing education established as major SAE service program
JL68-9-68 684594

Engineering education goals set realistically in final report
JL68-11-40 684605

Engine Oils see:

Crankcase Oils

Engines see:

Aircooled Engines
Compound Engines
Diesel Engines
Gasoline Engines
Industrial Engines
Racing Engines
Rocket Engines
Spark Ignition Engines
Steam Engines
Turbine Engines
Turbofan Engines
Turbojet Engines
Wankel Rotating Combustion Engine

Engine Tests

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Escape

Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Excavation see:

Two Stroke Cycle Engines

Exhaust Gases

New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Nitric oxide content of engine exhaust gas is a primary function of peak cycle temperatures and available oxygen
JL68-8-40 684576

Exhaust gas analysis used to figure fuel-air ratios
JL68-8-66 684584

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

F

Failure

Circular grid system permits a visual display of the magnitude and direction of the strain from point-to-point of a stamping
JL68-11-58 684610

Fans/Blowers

How, through engine and fan design, Pratt & Whitney was able to reduce high bypass ratio turbofan engine noise to an acceptable level
JL68-6-69 684561

Fasteners

Low carbon-boron steels favorably compared with SAE Grade 8, or medium carbon and alloy steels, also offer cold forming advantages
JL68-8-62 684583

Filament Reinforced Composites

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Finishing/Finishes

Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Fire Fighting

New York's super pumper fire-fighting system can deliver up to 10,000 gpm through five hose lines, replacing 10 ordinary pumpers and 40 feed lines
JL68-1-71 684504

Flight Control

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

Concorde has electrically signalled, hydraulically powered flight controls with a mechanical backup system
JL68-3-47 684523

All fluidic autopilot with fluid sensing logic and control circuits gives 3-axis control. Flight test results equal conventional units
JL68-4-41 684532

Navion airplane with variable aerodynamic and inertial properties allows safe in-flight evaluation of aircraft handling qualities
JL68-6-62 684558

Flight control servo actuator with clutchless over-power mechanism but no rate or position feedback offers increased power, lower cost
JL68-6-72 684562

Flight Simulation

Flight simulators will gain when motion system programs relate to body's motion cues
JL68-2-76 684519

Navion airplane with variable aerodynamic and inertial properties allows safe in-flight evaluation of aircraft handling qualities
JL68-6-62 684558

Flight Testing

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

Fluid Systems

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

All fluidic autopilot with fluid sensing logic and control circuits gives 3-axis control. Flight test results equal conventional units
JL68-4-41 684532

Fluidic Technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573

Friction Materials

SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

New test for brake linings gives reliable friction and wear data
JL68-7-50 684568

Fuel Additives

Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522

Fuel Cells

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Fuel Consumption

Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526

Fuel Injection

Engine changes highlight European car design for 1968
JL68-2-36 684508

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess
JL68-4-62 684536

Curtiss-Wright's rotary engine is light, compact, and smooth-running, characteristics which are usually associated with the aircraft gas turbine
JL68-5-67 684548

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Fuels see:

Gasoline

Fuel Systems see also:

Carburetors/Carburetion
Fuel Injection
Vapor Lock

New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527

Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

G

Gaging

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

Gaskets

Perforated steel strip laminated with Buta N asbestos forms a new cylinder head gasket for high output engines
JL68-9-50 684590

Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Gasoline

Bench test measures induction system deposit tendencies of fuels. Results do not correlate with those obtained by ASTM gum test now used.
JL68-2-50 684510

Chemical separation and identification of induction system deposit precursors permits new insight into the deposit forming mechanisms occurring in fuels
JL68-2-52 684511

Gasoline Engines

Engine changes highlight European car design for 1968
JL68-2-36 684508

Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526

Recommendations 4-7 of federal government report on control of air pollution
JL68-6-42 684553

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Nitric oxide content of engine exhaust gas is a primary function of peak cycle temperatures and available oxygen
JL68-8-40 684576

1969 passenger-car engineering trends
JL68-10-29 684596

Gears

see:

Differential Gears

Glass Fibers

Use of glass-reinforced composites for low-temperature basic jet engine components
JL68-3-72 684529

Governors

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Ground Effect Machines

Many options improve aircraft ground flotation more tires, wider tires, larger diameter tires, lower pressure tires, unconventional systems
JL68-9-43 684587

H

Heaters

Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Helicopters

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

Human Engineering

Human engineering has become a significant design tool
JL68-5-52 684545

Human engineering analysis is an aid to safe driving solutions
JL68-6-56 684556

Hydraulic Control

Concorde has electrically signalled, hydraulically powered flight controls with a mechanical backup system
JL68-3-47 684523

Hydraulic Fluids

Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

Hydraulic Motors

High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Hydraulic Systems

Surge brakes keep trailer braking synchronized with tow car braking
JL68-2-64 684516

Fluidic technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573

Hydraulic cranking starts Boeing 502-2E gas turbine in less than 3 sec without extensive engine modifications
JL68-8-44 684577

Hydromechanical Transmissions

Hydromechanical transmission shows its superior properties when tested in standard military truck
JL68-6-64 684559

I

Icing

Detectors predict formation of ice on roadway and bridge decks under both low and high humidity conditions
JL68-8-60 684582

Impact Sleds

Metal cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546

Impact Tests

Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500

Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525

Energy-absorbing steering column for small cars utilizes friction and plastic deformation
JL68-7-36 684565

Industrial Engines

Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534

Industrial Equipment

Fluidic technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573

Inspection

see also:

Quality Control

Tests on crosswire welds show that filletting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543

Instrumentation

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Instruments

see:

Aircraft Instruments Dynamometers Smokemeters

Insulation

Consideration of noise attenuation during design stage of turbine auxiliary power units gives most effective results
JL68-1-64 684502

Intake Systems

Bench test measures induction system deposit tendencies of fuels. Results do not correlate with those obtained by ASTM gum test now used.
JL68-2-50 684510

Chemical separation and identification of induction system deposit precursors permits new insight into the deposit forming mechanisms occurring in fuels.
JL68-2-52 684511

Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599

Involute Splines

New concept measures spline wear
JL68-3-70 684528

J

Jet Lift Aircraft

Use of glass-reinforced composites for low-temperature basic jet engine components
JL68-3-72 684529

Joints

Tests on crosswire welds show that filletting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543

L

Landing Gear

Many options improve aircraft ground flotation more tires, wider tires, larger diameter tires, lower pressure tires, unconventional systems
JL68-9-43 684587

Launch Vehicles

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Survey of eight reusable launch vehicles shows cost weight availability date and critical technologies
JL68-8-36 684575

Selective spring matching, proper orientation of lateral spring forces, two techniques to minimize payload tip-off
JL68-9-48 684589

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Life Support Systems

Proposed submersible is tailored to rescue submarine personnel
JL68-5-74 684550

Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

New cell design using concentrated phosphoric acid electrolyte electrolysis water vapor in spacecraft air to oxygen and hydrogen
JL68-11-62 684612

Logistics

Army GOER's, large rubber-tired articulated vehicles, have the mobility necessary for operations in Vietnam
JL68-11-44 684606

Lubricants

see:

Automatic Transmission Fluids
Crankcase Oils

Lubrication

Dry sump lubrication system with remote oil reservoir gives Ford Mark II GT increased oil capacity
JL68-1-78 684506

Lunar Environment

Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

M

Maintainability

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Management

Airline safety can be improved by consideration of psychological factors
JL68-2-49 684509

New problems challenge engineering management today
JL68-3-52 684524

Mathematical Analysis

Simple mathematical model shows how to increase cutting force reductions in horizontally vibrating plow blades
JL68-4-79 684541

Metal Forming

see also:

Casting
Cold forming
Stamping

Circular grid system permits a visual display of the magnitude and direction of the strain from point-to-point of a stamping
JL68-11-58 684610

Military Ground Power

300-W thermoelectric generator weighs less than 35 lb including fuel (diesel, kerosene or jet) for 8 hr operation under most conditions
JL68-6-66 684560

Spark ignition is more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608

Military Vehicle Mobility

Army GOER'S, large rubber-tired articulated vehicles, have the mobility necessary for operations in Vietnam
JL68-11-44 684606

Models

Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

Noise

Consideration of noise attenuation during design stage of turbine auxiliary power units gives most effective results
JL68-1-64 684502

How, through engine and fan design, Pratt & Whitney was able to reduce high bypass ratio turbofan engine noise to an acceptable level
JL68-6-69 684561

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

N

O

Orbital Transport

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Oxygen

New cell design using concentrated phosphoric acid electrolyte electrolysis water vapor in spacecraft air to oxygen and hydrogen
JL68-11-62 684612

P

Packaging

see:

Electronic Packaging

Paints

Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Passenger Car Design

Engine changes highlight European car design for 1968
JL68-2-36 684508

Prototype of New York safety car developed, using only available components or those under advanced development
JL68-4-44 684533

Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581

1969 passenger-car engineering trends
JL68-10-29 684596

Plastics

see also:

Reinforced Plastics

Low-cost power transistor-made by selecting appropriate encapsulant and encapsulating techniques—designed specifically for automotive circuits
JL68-4-66 684537

New fabricating techniques for plastics—solid-phase forming and structural foaming
JL68-6-36 684552

Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Porous Materials

see:

Powder Metallurgy/Powder Metals Powder Metallurgy/Powder Metals

When all recycle metal blended with virgin powder to form beryllium is vacuum melted cast and attritioned a better product is obtained
JL68-9-66 684593

Powerplants

see:

Aircooled Engines
Compound Engines
Diesel Engines
Gasoline Engines
Industrial Engines
Racing Engines
Rocket Engines
Spark Ignition Engines
Steam Engines
Thermoelectric Conversion
Turbine Engines
Turbofan Engines
Turbojet Engines
Two Stroke Cycle Engines

Power Transmission

see:

Axles
Clutches
Driveshafts
Gears
Shafts/Power
Transmissions

Pressurized Cabins

High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521

Private Aircraft

High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521

Pumps

see also:

Fuel Injection

New York's super pumper fire-fighting system can deliver up to 10,000 gpm through five hose lines, replacing 10 ordinary pumpers and 40 feed lines
JL68-1-71 684504

Dry sump lubrication system with remote oil reservoir gives Ford Mark II GT increased oil capacity
JL68-1-78 684506

High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Q

Quality Control

Tests on crosswire welds show that filletting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543

SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

R

Racing Cars

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Racing Engines

Dry sump lubrication system with remote oil reservoir gives Ford Mark II GT increased oil capacity
JL68-1-78 684506

Radar

Collision warning and display appears to be most important future use of airborne radar. Present systems are included in survey
JL68-1-76 684505

Reentry

Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Selective spring matching, proper orientation of lateral spring forces, two techniques to minimize payload tip-off
JL68-9-48 684589

Reinforced Plastics

Use of glass-reinforced composites for low-temperature basic jet engine components
JL68-3-72 684529

Reliability

see:

Aircraft Reliability

Research

see:

Crash Research

Retrorocket

Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Ride Evaluation

Dynamic response of vehicle traversing random rough surfaces is analyzed. Exponentially weighted filter detrends input road surface prior to classification
JL68-5-78 684551

Roads

Detectors predict formation of ice on roadway and bridge decks under both low and high humidity conditions
JL68-8-60 684582

Rocket Engines

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Rubber/Synthetic Rubber

Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

S

Safety

see:

Antiskid Devices Crash Research Driver Behavior Impact Sleds Seat Belts Vehicle Safety

Safety Devices

Surge brakes keep trailer braking synchronized with tow car braking
JL68-2-64 684516

Impact severity may be cut if occupant assumes a protective position prior to impact. Rules are given for safe use of seat belts
JL68-11-38 684604

Sandwich Structures

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Seals

see also:

Gaskets

High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521

Seat Belts

Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500

National bureau of standards will play important part in development of government vehicle safety standards
JL68-1-80 684507

Impact severity may be cut if occupant assumes a protective position prior to impact. Rules are given for safe use of seat belts
JL68-11-38 684604

Seats

Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525

Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581

Servomechanisms

Concorde has electrically signalled, hydraulically powered flight controls with a mechanical backup system
JL68-3-47 684523

Flight control servo actuator with clutchless over-power mechanism but no rate or position feedback offers increased power, lower cost
JL68-6-72 684562

Shafts/Power

see also:

Axles Driveshafts

Antifriction units, comprised of linear arrangements of ball or needle bearings may replace splined shafts to give truck driveline slip
JL68-1-68 684503

Silencers

Consideration of noise attenuation during design stage of turbine auxiliary power units gives most effective results
JL68-1-64 684502

Silicon

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Simulation

see:

Altitude Simulation Flight Simulation

Simulators

Collision warning and display appears to be most important future use of airborne radar. Present systems are included in survey
JL68-1-76 684505

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Metal cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546

Smokemeters

Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522

Soil Mechanics

Simple mathematical model shows how to increase cutting force reductions in horizontally vibrating plow blades
JL68-4-79 684541

Spacecraft Environment

New cell design using concentrated phosphoric acid electrolyte electrolysis water vapor in spacecraft air to oxygen and hydrogen
JL68-11-62 684612

Spacecraft Landings

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Space Environment

see:

Lunar Environment

Spark Ignition Engines

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Speed Control

see also:

Governors

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Springs

Selective spring matching, proper orientation of lateral spring forces, two techniques to minimize payload tip-off
JL68-9-48 684589

Stability

Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579

Stamping

Circular grid system permits a visual display of the magnitude and direction of the strain from point-to-point of a stamping
JL68-11-58 684610

Starters

Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534

Hydraulic cranking starts Boeing 502-2E gas turbine in less than 3 sec without extensive engine modifications
JL68-8-44 684577

Statistics

see:

Quality Control**Steam Engines**

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Steels

see also:

Carbon Steels

High-strength steel test truck goes places standard unit won't
JL68-2-66 684517

Surface finish is the main problem when continuous casting rimmed steels
JL68-11-31 684602

Steering

Three dimensionless quantities calculated from experimental tire data give steady-state directional control characteristics of vehicle
JL68-6-74 684563

Energy-absorbing steering column for small cars utilizes friction and plastic deformation
JL68-7-36 684565

Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571

1969 passenger-car engineering trends
JL68-10-29 684596

STOL Aircraft

Only deflected slipstream STOL aircraft, with its low cruise speed, matches DOC of today's jets, in design study
JL68-5-70 684549

Stresses

Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Stress Measurement

Circular grid system permits a visual display of the magnitude and direction of the strain from point-to-point of a stamping
JL68-11-58 684610

Submarines

Proposed submersible is tailored to rescue submarine personnel
JL68-5-74 684550

Superalloys

Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Supercharging/Superchargers

see also:

Turbocharging/Turbochargers

Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526

Supersonic Transports

Engineering problems associated with the SST, such as sonic boom, cosmic rays, fuel consumption, and airport requirements
JL68-1-60 684501

Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

Surfaces

Dynamic response of vehicle traversing random rough surfaces is analyzed. Exponentially weighted filter detrends input road surface prior to classification
JL68-5-78 684551

Suspension Systems

Engine changes highlight European car design for 1968
JL68-2-36 684508

1969 Passenger-car engineering trends
JL68-10-29 684596

Swept Wings

Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

T**Test Equipment**

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

Automatic transmission fluids rated for oxidation resistance by new aluminum beaker test
JL68-4-59 684535

SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

Testing

see:

Engine Tests**Flight Testing****Impact Tests****Wind Tunnel Testing****Tests**

Bench test measures induction system deposit tendencies of fuels. Results do not correlate with those obtained by ASTM gum test now used.
JL68-2-50 684510

New test for brake linings gives reliable friction and wear data
JL68-7-50 684568

Thermoelectric Conversion

300-W thermoelectric generator weighs less than 35 lb including fuel (diesel, kerosene or jet) for 8 hr operation under most conditions
JL68-6-66 684560

Tires

National bureau of standards will play important part in development of government vehicle safety standards
JL68-1-80 684507

Tire designed for emergency use is collapsible and stores flat, conserving trunk space
JL68-2-60 684514

Three dimensionless quantities calculated from experimental tire data give steady-state directional control characteristics of vehicle
JL68-6-74 684563

Wide base tire for light trucks significantly improves vehicle performance. One wheel and rim diameter simplifies tire and rim choice
JL68-7-48 684567

Many options improve aircraft ground flotation: more tires, wider tires, larger diameter tires, lower pressure tires, unconventional systems
JL68-9-43 684587

Tire variables affecting wet—stopping and cornering—traction, including the case of hydroplaning
JL68-9-58 684592

1969 passenger-car engineering trends
JL68-10-29 684596

Titanium

Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574

Titanium Alloys

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Traffic Engineering

see:

Roads**Trailers**

Surge brakes keep trailer braking synchronized with tow car braking
JL68-2-64 684516

Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571

Training Equipment

Collision warning and display appears to be most important future use of airborne radar. Present systems are included in survey
JL68-1-76 684505

Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

Transistors

Low-cost power transistor—made by selecting appropriate encapsulant and encapsulating techniques—designed specifically for automotive circuits
JL68-4-66 684537

Transmissions

see also:

Clutches

Engine changes highlight European car design for 1968
JL68-2-36 684508

Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

1969 passenger-car engineering trends
JL68-10-29 684596

Transport Aircraft see:

Supersonic Transports

Transportation

How U.S. aims to achieve coordinated transportation system
JL68-7-62 684570

Truck Design

Antifriction units, comprised of linear arrangements of ball or needle bearings may replace splined shafts to give truck driveline slip
JL68-1-68 684503

High-strength steel test truck goes places standard unit won't
JL68-2-66 684517

Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Truck Operation/Truck Performance

Hydromechanical transmission shows its superior properties when tested in standard military truck
JL68-6-64 684559

Army GOER's, large rubber-tired articulated vehicles, have the mobility necessary for operations in Vietnam
JL68-11-44 684606

Turbine Blades

Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Turbine Engine Controls

Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534

Turbine Engines

see also:

Turbofan Engines

Turbojet Engines

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Comparison of a 3-shaft cycle turbine with a twin-spool compressor and a 2-shaft cycle as automotive powerplants
JL68-7-71 684572

Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613

Turbine Trucks

Comparison of a 3-shaft cycle turbine with a twin-spool compressor and a 2-shaft cycle as automotive powerplants
JL68-7-71 684572

Turbocharging/Turbochargers

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess
JL68-4-62 684536

Turbofan Engines

Use of glass-reinforced composites for low-temperature basic jet engine components
JL68-3-72 684529

How, through engine and fan design, Pratt & Whitney was able to reduce high bypass ratio turbofan engine noise to an acceptable level
JL68-6-69 684561

Turbojet Engines

Hydraulic cranking starts Boeing 502-2E gas turbine in less than 3 sec without extensive engine modifications
JL68-8-44 684577

Two Stroke Cycle Engines

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess
JL68-4-62 684536

V

Vacuum Processing

When all recycle metal blended with virgin powder to form beryllium is vacuum melted cast and attritioned a better product is obtained
JL68-9-66 684593

Vapor Lock

Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

Vehicle Directional Control

Human engineering analysis is an aid to safe driving solutions
JL68-6-56 684556

Three dimensionless quantities calculated from experimental tire data give steady-state directional control characteristics of vehicle
JL68-6-74 684563

Vehicle Performance

Comparison of a 3-shaft cycle turbine with a twin-spool compressor and a 2-shaft cycle as automotive powerplants
JL68-7-71 684572

Vehicle Safety

Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500

National bureau of standards will play important part in development of government vehicle safety standards
JL68-1-80 684507

Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525

Prototype of New York safety car developed, using only available components or those under advanced development
JL68-4-44 684533

Energy-absorbing steering column for small cars utilizes friction and plastic deformation
JL68-7-36 684565

Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579

Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581

Vehicle safety problems and opportunities are both acute
JL68-9-46 684588

Impact severity may be cut if occupant assumes a protective position prior to impact. Rules are given for safe use of seat belts
JL68-11-38 684604

Vibration

Simple mathematical model shows how to increase cutting force reductions in horizontally vibrating plow blades
JL68-4-79 684541

Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

VTOL Aircraft

see:

Helicopters

W

Wankel Rotating Combustion Engine

Engine changes highlight European car design for 1968
JL68-2-36 684508

Curtiss-Wright's rotary engine is light, compact, and smooth-running, characteristics which are usually associated with the aircraft gas turbine
JL68-5-67 684548

Warning Systems

Collision warning and display appears to be most important future use of airborne radar. Present systems are included in survey
JL68-1-76 684505

Warranties

Detectors predict formation of ice on roadway and bridge decks under both low and high humidity conditions
JL68-8-60 684582

Wear

New concept measures spline wear
JL68-3-70 684528

New test for brake linings gives reliable friction and wear data
JL68-7-50 684568

Welding

New parallel gap welding electrode with integral heat sink eliminates overheating problems in joining flat pack leads to circuit boards
JL68-2-57 684513

Mechanical thermal pulse bonding controls process energies accurately and dynamically
JL68-3-79 684530

Tests on crosswire welds show that filletting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543

Welding of low-carbon steels by electron beam process possible on a commercial basis once certain precautions are followed
JL68-9-70 684595

Wind Tunnel Testing

Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571

Wings/Aircraft

see also:

Swept Wings

Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

SAE JOURNAL AUTHOR INDEX

SAE JOURNAL—JANUARY THROUGH DECEMBER, 1968—VOL 76

A

- Ahrens, W. H.**
Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526
- Allbert, B. J.**
Tire variables affecting wet—stopping and cornering—traction, including the case of hydroplaning
JL68-9-58 684592
- Amann, C. A.**
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554
- Anderson, A. E.**
New test for brake linings gives reliable friction and wear data
JL68-7-50 684568
- Andrews, D.**
Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603
- Armstrong, R. W.**
National Bureau of Standards will play important part in development of government vehicle safety standards
JL68-1-80 684507
- Aronson, R. R.**
Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600
- Asano, S.**
Energy-absorbing steering column for small cars utilizes friction and plastic deformation
JL68-7-36 684565
- Aschenbrenner, F. A.**
New problems challenge engineering management today
JL68-3-52 684524
- Aufderhaar, W. B.**
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554
- Ayres, R. U.**
Alternate powerplants to solve air pollution include steam engines, hybrid systems, electric propulsion, and fuel cells
JL68-12-40 684613
- B**
- Baird, J. D.**
Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525
- Banshoya, J.**
Energy-absorbing steering column for small cars utilizes friction and plastic deformation
JL68-7-36 684565
- Bates, J. A.**
Metal cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546
- Beauvais, F. N.**
Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571
- Benstein, E. H.**
Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534
- Berlin, J. I.**
Airline safety can be improved by consideration of psychological factors
JL68-2-49 684509
- Bester, M. H.**
Tests on crosswire welds show that filleting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543
- Biggers, B. H.**
New test for brake linings gives reliable friction and wear data
JL68-7-50 684568
- Blackburn, E. P.**
Attitude control system keeps vela spacecraft spinning to give zero momentum vehicle
JL68-9-52 684591
- Borlace, F. H.**
Flight simulators will gain when motion system programs relate to body's motion cues
JL68-2-76 684519
- Boulgarides, J. D.**
New problems challenge engineering management today
JL68-3-52 684524
- Bowers, J.**
Dry sump lubrication system with remote oil reservoir gives Ford Mark II GT increased oil capacity
JL68-1-78 684506
- Boyd, R. L.**
Collision warning and display appears to be most important future use of airborne radar. Present systems are included in survey
JL68-1-76 684505
- Boyd, A. S.**
How U.S. aims to achieve coordinated transportation system
JL68-7-62 684570
- Boyd, R. J.**
Simple mathematical model shows how to increase cutting force reductions in horizontally vibrating plow blades
JL68-4-79 684541
- Bradshaw, R. W.**
New problems challenge engineering management today
JL68-3-52 684524
- Brender, B. F.**
Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518
- Brink, H. M.**
Full-scale crash tests show that Liberty Mutual capsule seat protects passengers best
JL68-3-56 684525
- Brown, P.**
National Bureau of Standards will play important part in development of government vehicle safety standards
JL68-1-80 684507
- Bryant, R. D.**
Tests on crosswire welds show that filleting and embedment combine to form effective visual criteria for welded interconnections
JL68-5-44 684543
- Bucy, Jr., R. W.**
Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574
- Bundorf, R. T.**
Computer study shows hitching configuration affects the handling response of automobile-trailer combination to steer and wind at high speeds
JL68-7-64 684571
- Buttgereit, W.**
Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

C

- Canever, C. J.**
Engine/transaxle and braking units in Ford

MK II GT race car were developed on automatically controlled laboratory race simulators

JL68-2-70 684518

Cardenas, A.

Tire designed for emergency use is collapsible and stores flat, conserving trunk space

JL68-2-60 684514

Cejka, A.

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit

JL68-11-32 684603

Cichowski, W. G.

Impact severity may be cut if occupant assumes a protective position prior to impact. Rules are given for safe use of seat belts

JL68-11-38 684604

Ciemochowski, M. F.

Detectors predict formation of ice on roadway and bridge decks under both low and high humidity conditions

JL68-8-60 684582

Clarke, P. J.

New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses

JL68-3-66 684527

Clifford, J. E.

New cell design using concentrated phosphoric acid electrolyte electrolysis water vapor in spacecraft air to oxygen and hydrogen

JL68-11-62 684612

Coffman, P. M.

New fabricating techniques for plastics solid-phase forming and structural foaming

JL68-6-36 684552

Coffman, Q. H.

Los Angeles air pollution Rule 66 nips air pollution due to solvents

JL68-11-25 684601

Collet, P. J.

Comparison of a 3-shaft cycle turbine with a twin-spool compressor and a 2-shaft cycle as automotive powerplants

JL68-7-71 684572

Compton, W. A.

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts

JL68-8-53 684580

Comstock, Lt. Col., K. G.

Army GOER's, large rubber-tired articulated vehicles, have the mobility necessary for operations in Vietnam

JL68-11-44 684606

Cushman, R. H.

Mechanical thermal pulse bonding controls process energies accurately and dynamically

JL68-3-79 684530

D

Danforth, J. P.

Increased energy absorption by car interior can help reduce injuries from car crashes

JL68-11-52 684500

Darrieus, B.

Concorde has electrically signalled, hydraulically powered flight controls with a mechanical backup system

JL68-3-47 684523

Dawes, C. J.

New parallel gap welding electrode with integral heat sink eliminates overheating problems in joining flat pack leads to circuit boards

JL68-2-57 684513

Deplante, H.

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit

JL68-11-32 684603

Dias, J. J.

Consideration of noise attenuation during design stage of turbine auxiliary power units gives most effective results

JL68-1-64 684502

Digges, K. H.

Many options improve aircraft ground flotation—more tires, wider tires, larger diameter tires, lower pressure tires, unconventional systems

JL68-9-43 684587

Dimitroff, E.

Chemical separation and identification of induction system deposit precursors permits new insight into the deposit forming mechanisms occurring in fuels

JL68-2-52 684511

Dindorfer, W.

Low-cost control systems needed to make industrial gas turbines competitive with diesel

JL68-4-55 684534

Dolowy, Jr., J. F.

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts

JL68-8-53 684580

Dooley, J. L.

Inexpensive turbosupercharging, fuel injection, and modern plugs and ignition systems may revive 2-stroke for below 300-bhp aircraft duty excess

JL68-4-62 684536

Dorgan, R.

Hydromechanical transmission shows its superior properties when tested in standard military truck

JL68-6-64 684559

Dorn, W. M.

Los Angeles air pollution Rule 66 nips air pollution due to solvents

JL68-11-25 684601

Douglass, B.

Surge brakes keep trailer braking synchronized with tow car braking

JL68-2-64 684516

Dunlap, D. R.

Metal cutting proves successful method of absorbing energy of crash-impact simulators

JL68-5-54 674546

Dunlap, J. W.

Human engineering has become a significant design tool

JL68-5-52 684545

Dutzmann, R. J.

Selective spring matching, proper orientation of lateral spring forces, two techniques to minimize payload tip-off

JL68-9-48 684589

Dyment, J. T.

Engineering problems associated with the SST, such as sonic boom, cosmic rays, fuel consumption, and airport requirements

JL68-1-60 684501

E

Eastman, J. B.

Low-cost control systems needed to make industrial gas turbines competitive with diesel

JL68-4-55 684534

Eaton, J. M.

Only deflected slipstream STOL aircraft, with its low cruise speed, matches DOC of today's jets, in design study

JL68-5-70 684549

Ellis, D. R.

Navion airplane with variable aerodynamic and inertial properties allows safe in-flight evaluation of aircraft handling qualities

JL68-6-62 684558

Eltinge, L.

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape

JL68-9-28 684586

Erickson, P. J.

New York's super pumper fire-fighting system can deliver up to 10,000 gpm through five hose lines, replacing 10 ordinary pumpers and 40 feed lines

JL68-1-71 684504

Ertle, L. J.

Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop

JL68-4-68 684538

F

Fagley, Jr., W. S.

Exhaust gas analysis used to figure fuel-air ratios

JL68-8-66 684584

- Finch, D. M.**
Metal cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546
- Fletcher, K. L.**
New aluminum-cored printed circuit board, with copper-clad teflon-fiberglass dielectric layers has good heat, dielectric, and strength properties
JL68-2-63 684515
- Foote, L. R.**
Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600
- Francis, R. H.**
Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603
- Fuller, L. J.**
Los Angeles air pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- Furia, A.**
Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579
- Furman, P. H.**
High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521
- G**
- Gadd, C. W.**
Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500
- Gagliardi, J. C.**
Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599
- Gancel, P.**
Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579
- Garabedian, C. G.**
Spark ignition is a more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608
- Garrard, W. C. J.**
Only deflected slipstream STOL aircraft, with its low cruise speed, matches DOC of today's jets, in design study
JL68-5-70 684549
- Gealer, R. L.**
New test for brake linings gives reliable friction and wear data
JL68-7-50 684568
- Gehl, J. H.**
New fabricating techniques for plastics solid-phase forming and structural foaming
JL68-6-36 684552
- George, J. C.**
Los Angeles air pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- Gerrard, J. E.**
New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527
- Gill, F. L.**
Low carbon-boron steels favorably compared with SAE Grade 8, or medium carbon and alloy steels, also offer cold forming advantages
JL68-8-62 684583
- Golothan, D. W.**
Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522
- Gomersall, E. W.**
Survey shows weight savings possible with various combinations of materials Al, Ti and Be and wall constructions in large launchers
JL68-7-82 684574
- Gordanier, M.**
Hydromechanical transmission shows its superior properties when tested in standard military truck
JL68-6-64 684559
- Gratch, S.**
New test for brake linings gives reliable friction and wear data
JL68-7-50 684568
- Grant, R. T.**
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554
- Griswold, S. S.**
Los Angeles air pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- H**
- Hagan, J. W.**
Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598
- Hamkins, L. R.**
Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586
- Hamming, W. J.**
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- Hayes, H. P.**
New test for brake linings gives reliable friction and wear data
JL68-7-50 684568
- Hayes, J. G.**
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- Henke, R.**
Fluidic technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573
- Herndon, W. B.**
SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555
- Hight, P. V.**
Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581
- Hirsch, C. E.**
New problems challenge engineering management today
JL68-3-52 684524
- Hittler, D. L.**
Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586
- Horning, D. O.**
Metal cutting proves successful method of absorbing energy of crash-impact simulators
JL68-5-54 674546
- Houke, R. E.**
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601
- Howells, H. E.**
Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522
- Hull, L. E.**
Hydraulic cranking starts Boeing 502-2E gas turbine in less than 3 sec without extensive engine modifications
JL68-8-44 684577
- Huls, T. A.**
Nitric oxide content of engine exhaust gas is a primary function of peak cycle temperatures and available oxygen
JL68-8-40 684576

I

Ihnacik, Jr., J. I.
Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

J

James, G. E.
Spark ignition is a more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608

Johnson, J. R.
Engine/transaxle and braking units in Ford MK II GT race car were developed on automatically controlled laboratory race simulators
JL68-2-70 684518

Johnston, A.
Bench test measures induction system deposit tendencies of fuels. Results do not correlate with those obtained by ASTM gum test now used
JL68-2-50 684510

Jones, C.
Curtiss-Wright's rotary engine is light, compact, and smooth-running, characteristics which are usually associated with the aircraft gas turbine
JL68-5-67 684548

Jones, J. H.
Premixed and preheated mixtures aid air-fuel distribution study
JL68-10-72 684599

K

Kalen, S. E.
Human engineering has become a significant design tool
JL68-5-52 684545

Kasak, A. J.
Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Keeler, S. P.
Circular grid system permits a visual display of the magnitude and direction of the strain from point-to-point of a stamping
JL68-11-58 684610

Keen, J. M. S.
Use of glass-reinforced composites for low-temperature basic jet engine components
JL68-3-72 684529

Kelley, Jr., J. D.
Tire variables affecting wet—stopping and cornering—traction, including the case of hydroplaning
JL68-9-58 684592

Kendall, R. T.
Emergency escape system could return orbiting astronauts safely to earth. The system makes both ground- and water-landings
JL68-8-68 684585

Ker, R. A. C.
Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

Kern, R. D.
Electrical unit controls electro-vacuum actuator in speed control for auxiliaries driven off truck engines
JL68-8-46 684578

Kessler, F. J.
Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Kester, J. D.
How, through engine and fan design, Pratt & Whitney was able to reduce high bypass ratio turbofan engine noise to an acceptable level
JL68-6-69 684561

King, B.
When all recycle metal blended with virgin powder to form beryllium is vacuum melted cast and attritioned a better product is obtained
JL68-9-66 684593

King, J. R.
Welding of low-carbon steels by electron beam process possible on a commercial basis once certain precautions are followed
JL68-9-70 684595

Kirby, D. C.
Attitude control system keeps vela spacecraft spinning to give zero momentum vehicle
JL68-9-52 684591

Kottmeyer, R. E.
Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Kroell, C. K.
Increased energy absorption by car interior can help reduce injuries from car crashes
JL68-1-52 684500

L

Lambrecht, J.
Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Larborn, A. O. J.
Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Last, L. R.
Portable analyzer detects/evaluates in jet engines by examining vibration and noise inputs
JL68-7-59 684569

Latson, D. M.
Hydromechanical transmission shows its superior properties when tested in standard military truck
JL68-6-64 684559

Laumeister, B. R.
Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600

Lehoczky, Jr., J.
New York's Super Pumper fire-fighting system can deliver up to 10,000 gpm through five hose lines, replacing 10 ordinary pumps and 40 feed lines
JL68-1-71 684504

Lillis, S. M.
Perforated steel strip laminated with Buta N asbestos forms a new cylinder head gasket for high output engines
JL68-9-50 684590

Lunche, R. G.
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601

Lynes, A. E.
Ford, General Electric, and Electric Fuel Propulsion electric cars suffer from range and refueling time limitations
JL68-11-20 684600

M

Macura, J. F.
Dry sump lubrication system with remote oil reservoir gives Ford Mark II GT increased oil capacity
JL68-1-78 684506

Malone, T. F.
Vehicle safety problems and opportunities are both acute
JL68-9-46 684588

Marsee, F. J.
Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Marsh, F. E.
Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

Marshall, H. P.
Improved internal combustion engine electives can change student-faculty attitudes
JL68-4-74 684539

Martin, D. E.
Increased energy absorption by car interior

can help reduce injuries from car crashes
JL68-1-52 684500

Martland, L.
Ford, General Electric, and Electric Fuel
Propulsion electric cars suffer from range
and refueling time limitations
JL68-11-20 684600

McCarron, G. E.
Dynamic response of vehicle traversing ran-
dom rough surfaces is analyzed. Exponen-
tially weighted filter detrends input road
surface prior to classification
JL68-5-78 684551

McCarthy, J. F.
New problems challenge engineering man-
agement today
JL68-3-52 684524

McConnell, G.
Influence of fuel properties and effect of
antismoke additives on diesel exhaust smoke
JL68-3-36 684522

McLean, A. F.
Superalloy castings are meeting small-tur-
bine blade life needs
JL68-6-51 684554

Meek, J. F.
Engine/transaxle and braking units in Ford
MK II GT race car were developed on auto-
matically controlled laboratory race simu-
lators
JL68-2-70 684518

Metcalfe, A. G.
High-strength, heat-resistant metal-matrix
composites save weight in aerospace parts
JL68-8-53 684580

Michaels, R.
Human engineering analysis is an aid to
safe driving solutions
JL68-6-56 684556

Michaels, R. M.
Human engineering has become a significant
design tool
JL68-5-52 684545

Munford, J. A.
Tests on crosswire welds show that filletting
and embedment combine to form effective
visual criteria for welded interconnections
JL68-5-44 684543

Miller, C. O.
Influence of fuel properties and effect of
antismoke additives on diesel exhaust smoke
JL68-3-36 684522

Miller, G. E.
Navion airplane with variable aerodynamic
and inertial properties allows safe in-flight
evaluation of aircraft handling qualities
JL68-6-62 684558

Miller, Jr., J. W.
New concept measures spline wear
JL68-3-70 684528

Monti, I. J.
Engine/transaxle and braking units in Ford
MK II GT race car were developed on auto-
matically controlled laboratory race simu-
lators
JL68-2-70 684518

Morris, G. R.
Los Angeles Air Pollution Rule 66 nips air
pollution due to solvents
JL68-11-25 684601

Moyes, E. R.
New problems challenge engineering man-
agement today
JL68-3-52 684524
Ford, General Electric, and Electric Fuel
Propulsion electric cars suffer from range
and refueling time limitations
JL68-11-20 684600

N

Nahum, A. M.
Much can be done to make riding in the
back seat safer—but beware of untested
changes
JL68-8-58 684581

Nalezny, C. L.
Simple mathematical model shows how to
increase cutting force reductions in hori-
zontally vibrating plow blades
JL68-4-79 684541

Nau, R. A.
Survey of eight reusable launch vehicles
shows cost weight availability date and
critical technologies
JL68-8-36 684575

Neild, A. B.
300-W thermoelectric generator weighs less
than 35 lb including fuel (diesel, kerosene
or jet) for 8 hr operation under most con-
ditions
JL68-6-66 684560

Nelson, C. E.
Continuing education established as major
SAE service program
JL68-9-68 684594

Newell, G. C.
Reliability and maintainability goals for
wing sweep actuation system of Boeing
supersonic transport
JL68-5-36 684542

Newhall, H. K.
Spark ignition is a more satisfactory way to
aid combustion of hand-to-burn ammonia
in diesel engines than diesel pilot fuel.
Direct injection of pure ammonia isn't at
all practical
JL68-11-49 684608

Nickol, H. A.
Nitric oxide content of engine exhaust gas
is a primary function of peak cycle tempera-
tures and available oxygen
JL68-8-40 684576

Nishioka, K.
Survey shows weight savings possible with

various combinations of materials Al, Ti
and Be and wall constructions in large
launchers
JL68-7-82 684574

Nordeen, D. L.
Three dimensionless quantities calculated
from experimental tire data give steady-state
directional control characteristics of vehicle
JL68-6-74 684563

Nunez, R. R.
Exhaust gas analysis used to figure fuel-air
ratios
JL68-8-66 684584

O

O'Hagen, J. T.
New York's Super Pumper fire-fighting sys-
tem can deliver up to 10,000 gpm through
five hose lines, replacing 10 ordinary pump-
ers and 40 feed lines
JL68-1-71 684504

Okamoto, K.
Energy-absorbing steering column for small
cars utilizes friction and plastic deformation
JL68-7-36 684565

Okoshi, H.
Energy-absorbing steering column for small
cars utilizes friction and plastic deformation
JL68-7-36 684565

Oliver, D.
Low-cost control systems needed to make
industrial gas turbines competitive with
diesel
JL68-4-55 684534

Onewein, L. J.
Reliability and maintainability goals for
wing sweep actuation system of Boeing
supersonic transport
JL68-5-36 684542

O'Reilly, J. B.
High-flying, small aircraft still feature sim-
ple controls, but with pressurization special
problems arise
JL68-2-80 684521

P

Parsons, S. O.
Astronauts need practice to perform mainte-
nance tasks under lunar gravity effects
JL68-11-46 684607

Pearsall, T. J.
Spark ignition is a more satisfactory way to
aid combustion of hand-to-burn ammonia
in diesel engines than diesel pilot fuel.
Direct injection of pure ammonia isn't at
all practical
JL68-11-49 684608

Pearson, B. A.
Automatic transmission fluids rated for oxi-
dation resistance by new aluminum beaker
test
JL68-4-59 684535

Pelz, D. C.
Dangerous young drivers—why they are unsafe, and how their driving behavior can be improved by remedial programs
JL68-10-61 684597

Penny, N.
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Percival, W. H.
Intermittent power augmentation device supercharges engine when maximum power is required, without affecting fuel economy
JL68-3-62 684526

Perrier, P.
Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Petersons, A. V.
Many options improve aircraft ground flotation—more tires, wider tires, larger diameter tires, lower pressure tires, unconventional systems
JL68-9-43 684587

Pietkiewicz, C. J.
Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

Platt, M.
Engine changes highlight European car design for 1968
JL68-2-36 684508

Precht, H.
Surface finish is the main problem when continuous casting rimmed steels
JL68-11-31 684602

Preston, J.
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Preston, T.
Surface finish is the main problem when continuous casting rimmed steels
JL68-11-31 684602

R

Raia, E.
1969 Passenger-car engineering trends
JL68-10-29 684596

Richardson, F. D.
Low-cost power transistor-made by selecting appropriate encapsulant and encapsulating techniques—designed specifically for automotive circuits
JL68-4-66 684537

Rio, R. L.
Hydromechanical transmission shows its superior properties when tested in standard military truck
JL68-6-64 684559

Ross, W. D.
SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

Ryan, W. J.
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601

S

San Filippo, V. C.
New problems challenge engineering management today
JL68-3-52 684524

Santo, H. A.
High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Hydraulic cranking starts Boeing 502-2E gas turbine in less than 3 sec without extensive engine modifications
JL68-8-44 684577

Schachter, S.
Disc brakes on all wheels plus modulating valves improve overall braking stability of lighter European car. Rear wheel skid in particular is prevented
JL68-8-49 684579

Schafer, E.
Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Schiller, C.
Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Schmitz, G. K.
High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Schuman, S. H.
Dangerous young drivers—why they are unsafe, and how their driving behavior can be improved by remedial programs
JL68-10-61 684597

Seminara, J. L.
Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

Senior, Jr., G. A.
Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Severy, D. M.
Full-scale crash tests show that Liberty

Mutual capsule seat protects passengers best
JL68-3-56 684525

Sharp, W. H.
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Shavelson, R. J.
Astronauts need practice to perform maintenance tasks under lunar gravity effects
JL68-11-46 684607

Shidle, N. G.
Engineering education goals set realistically in final report
JL68-11-40 684605

Shiffler, R. W.
Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

Shimizu, H.
High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Sidles, J.
Tire designed for emergency use is collapsible and stores flat, conserving trunk space
JL68-2-60 684514

Siegel, A. W.
Much can be done to make riding in the back seat safer—but beware of untested changes
JL68-8-58 684581

Siemietowski, J.
Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Silbert, P. L.
SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

Silver, J. N.
Impact severity may be cut if occupant assumes a protective position prior to impact. Rules are given for safe use of seat belts
JL68-11-38 684604

Sipple, H. E.
Los Angeles Air Pollution Rule 66 nips air pollution due to solvents
JL68-11-25 684601

Skarstrom, C. W.
New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527

Slabiak, W.
High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Slade, P. M.

Low-cost control systems needed to make industrial gas turbines competitive with diesel
JL68-4-55 684534

Slaiby, T. G.

How, through engine and fan design, Pratt & Whitney was able to reduce high bypass ratio turbofan engine noise to an acceptable level
JL68-6-69 684561

Smith, G. R.

SAE No. 2 friction test fixture can also be used as a quality control tool
JL68-6-53 684555

Smith, T. W.

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Smoley, E. M.

Thermal loads in nonmetallic gaskets may compensate for bolt load losses due to stress relaxation in the gasket
JL68-11-56 684609

Spadone, D. M.

Proposed submersible is tailored to rescue submarine personnel
JL68-5-74 684550

Spiers, J.

Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522

Starkman, E. S.

Spark ignition is a more satisfactory way to aid combustion of hand-to-burn ammonia in diesel engines than diesel pilot fuel. Direct injection of pure ammonia isn't at all practical
JL68-11-49 684608

Stephens, B. W.

Human engineering analysis is an aid to safe driving solutions
JL68-6-56 684556

Stephens, B. W.

Human engineering has become a significant design tool
JL68-5-52 684545

Steele, M.

1969 passenger-car engineering trends
JL68-10-29 684596

Steward, K. P.

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Strigle, C. E.

Wide base tire for light trucks significantly improves vehicle performance. One wheel and rim diameter simplifies tire and rim choice
JL68-7-48 684567

Sturos, J. A.

Electro-hydraulic unit with closed loop control has integral computer to gage dynamic rate and damping coefficient of rubber parts being excited
JL68-2-78 684520

Sullivan, P. B.

Evidence varies as to whether less hygroscopic brake fluids have advantages in service. They are designed to reduce boiling point drop
JL68-4-68 684538

Swain, J. C.

High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Swihart, J. M.

Reliability and maintainability goals for wing sweep actuation system of Boeing supersonic transport
JL68-5-36 684542

T**Taft, C. K.**

Fluidic technology necessary to control off-the-road vehicles is available now. Development work remains to be done
JL68-7-78 684573

Taylor, R. J.

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Thomas, D. L.

High-speed, variable-displacement vane pump developed for vehicle transmissions features pivoting-tip vanes and a deformable cam ring
JL68-6-79 684564

Thompson, J. L.

Automatic transmission fluids rated for oxidation resistance by new aluminum beaker test
JL68-4-59 684535

Tolle, H.

Various concepts for European reusable launch vehicle are presented. 3 tons will be put into 300-nautical mile polar orbit
JL68-11-32 684603

Trompler, D. H.

High-flying, small aircraft still feature simple controls, but with pressurization special problems arise
JL68-2-80 684521

V**Van Deusen, B. D.**

Dynamic response of vehicle traversing random rough surfaces is analyzed. Exponentially weighted filter detrends input road surface prior to classification
JL68-5-78 684551

Vardi, J.

New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527

Vetter, L. J.

Flight control servo actuator with clutchless overpower mechanism but no rate or position feedback offers increased power, lower cost
JL68-6-77 684562

All fluidic autopilot with fluid sensing logic and control circuits gives 3-axis control. Flight test results equal conventional units
JL68-4-41 684532

Voges, C. H.

Volkswagen's 1600 engines have electronically controlled fuel injection units. Emissions meet requirements with no performance loss
JL68-6-58 684557

Vulliamy, M.

Influence of fuel properties and effect of antismoke additives on diesel exhaust smoke
JL68-3-36 684522

W**Wachtell, R. L.**

Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Wade, D. T.

New device uses controlled absorption-desorption cycling phased to engine operation to eliminate carburetor and tank evaporative losses
JL68-3-66 684527

Wakamiya, Y.

Attitude control system keeps vela spacecraft spinning to give zero momentum vehicle
JL68-9-52 684591

Warren, A. J.

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

Webb, B. A.

High-strength, heat-resistant metal-matrix composites save weight in aerospace parts
JL68-8-53 684580

Weidner, Jr., H. C.

Low carbon-boron steels favorably compared with SAE Grade 8, or medium car-

bon and alloy steels, also offer cold forming advantages
JL68-8-62 684583

Welk, Jr., H. B.

Fluidic stability augmentation system with two subsystems is to be flight tested in Boeing CH-46A helicopter
JL68-2-55 684512

Wentworth, J. T.

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

White, W. H.

Attitude control system keeps vela spacecraft spinning to give zero momentum vehicle
JL68-9-52 684591

Whitston, C. W.

New problems challenge engineering management today
JL68-3-52 684524

Wiesman, D. H.

Nonaqueous acrylic dispersion, perhaps the next generation of automotive finishes, combine best features of acrylic enamels and lacquers
JL68-10-69 684598

Wilson, J. C.

Turbine meter accurately measures rate of fuel usage and total fuel used in business aircraft
JL68-11-61 684611

Wokoun, W.

Human engineering has become a significant design tool
JL68-5-52 684545

Wood, H. J.

Superalloy castings are meeting small-turbine blade life needs
JL68-6-51 684554

Y

Young, J. R.

Antifriction units, comprised of linear arrangements of ball or needle bearings may replace splined shafts to give truck driveline slip
JL68-1-68 684503

Z

Zackrisson, F. E. S.

Emission control via engine modification (no secondary systems used as aids). Focuses on induction system, combustion chamber shape
JL68-9-28 684586

1968 SAE JOURNAL INDEX

PUBLISHED BY THE SOCIETY OF AUTOMOTIVE ENGINEERS, INC.
TWO PENNSYLVANIA PLAZA, N.Y., N.Y. 10001

